


5321

- Load rating up to 150kg
- 100%+ extension
- 19.1mm slide thickness
- Hold-in
- Optional bracket accessory kits for various mounting options



- Charge jusqu'à 150kg
- Course + 100%
- Épaisseur de glissière de 19,1mm
- Point dur en position fermée
- Kits d'accessoires d'équerres en option pour convenir aux divers types de montage

- Lastwert bis 150kg
- Überauszug
- 19,1mm Schienendicke
- Rastung in geschlossener Position
- Optionale Winkelzubehörsätze für diverse Montagemöglichkeiten



5321	mm										kg	
	SL	TR	A	B	C	D	E	F	G	H	W	L
DZ5321-0030	300	323.5	-	-	-	192	224	-	-	-	1.80	120
DZ5321-0035	350	373.5	-	-	-	224	256	-	-	-	2.07	120
DZ5321-0040	400	423.5	-	160	192	288	320	128	160	-	2.37	130
DZ5321-0045	450	473.5	-	160	192	320	352	128	160	-	2.70	140
DZ5321-0050	500	523.5	-	192	224	384	416	160	192	-	3.00	150
DZ5321-0055	550	573.5	-	192	224	416	448	160	192	-	3.31	140
DZ5321-0060	600	623.5	-	256	288	480	512	192	256	-	3.62	120
DZ5321-0070-A	700	723.5	288	320	544	576	608	256	288	544	4.26	110
DZ5321-0080-A	790	803.5	-	352	384	672	704	320	352	384	4.80	100
DZ5321-0090-A	900	923.5	-	448	480	768	800	352	384	416	5.57	80
DZ5321-0100-A	1000	1023.5	448	480	512	864	896	448	480	-	6.19	70
DZ5321-0110-A	1100	1123.5	448	544	576	992	1024	448	480	512	6.81	60

Notes:

- Fixing recommendation: M5 countersunk/ 6mm countersunk Euro screw
- For bracket accessory kit see 635xx

Notes:

- Visserie recommandée: M5 tête fraisée/ Eurovis à tête fraisée diamètre 6mm
- Pour le kit d'accessoires d'équerres, voir 635xx

Hinweise:

- Empfohlene Befestigung: M5 Senkkopfschraube/ Euro-Senkkopfschraube 6mm
- Winkelzubehörsatz siehe 635xx



DZ635xx