


## POB180 (SINGLE-PHASE) CONCRETE GRINDER • 180 MM



- Ergonomic handles for greater comfort when working.
- Soft start with electronic speed variator to adapt the rotation speed to your work.
- Start trigger with lock-on button for continuous work, and power-off protection.
- Toolless detachable brush segment (magnetic) for sanding in corners.
- Integrated exhaust function.
- For sanding, smoothing and dry deburring of building materials (concrete, natural stone, granite, marble, mortar), and for removing adhesive and protective plaster residues.



Toolless detachable  
brush segment (magnetic)



Integrated exhaust  
function

WARRANTY	2
Voltage/Frequency	230 V / 50 Hz
Motor power	1900 W
Rotation speed	500 ~ 3000 rpm
Diamond cup diameter	Ø 180 mm
Diamond cup bore	Ø 22.23 mm
Diamond cup fixing	M8 x 30 mm screw
Protection index	IPX0
Protection class	II
Suction outlet	Ø 42 mm
Sound pressure LpA	98.2 dB (A) no load
Sound power LwA	109.2 dB (A) no load
Vibrations in hands/arms	4.8 m/s <sup>2</sup>
Net weight	6,920 kg (with diamond cup)
Gross weight	8 kg
Dimensions	395 x 235 x 295 mm
Packing dimensions	440 x 235 x 330 mm
Spare parts reference	600400 (+ N°/ exploded view)
Gencod	3661589107442

### ACCESSORIES AND OPTIONS

- The machine comes with a Ø180 mm double-rim diamond cup, service spanners and instructions manual.

CONSUMABLES

1500178 P. 17  
1100178 P. 18  
976 P. 18